DGGB110P

110 kVA

ROUNDED CATALOGUE CLASS

Perkins diesel generator | Open set

NEW DIESEL GENERATOR RANGE

ENGINE PLATFORM

Perkins

1104C-44TAG2

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Perkins 1104C-44TAG2

ALTERNATOR

Stamford UCI274C1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

100 kVA 80 kW

STANDBY POWER / ESP

110 kVA 88 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The DGGB model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	109	87	100	80
200	PS	110	88	100	80
208	PS	110	88	100	80
220	SD	109	87	100	80
230	SD	110	88	100	80
240	SD	110	88	100	80
380	SS	109	87	100	80
400	SS	110	88	100	80
415	SS	110	88	100	80

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Exact build, performance and delivery scope are confirmed in the quotation.

Technical specification

DGGB110P | Perkins 1104C-44TAG2 | Open set

ENGINE

Manufacturer	Perkins
Model	1104C-44TAG2
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	4
Arrangement	In Line
Displacement	4.4L
Bore	105mm
Stroke	127mm
Compression ratio	18.3:1
Cooling	Liquid Cooled
Coolant capacity	12.6L
Oil capacity	8.0L

ALTERNATOR

Manufacturer	Stamford
Model	UCI274C1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD	75% LOAD	100% LOAD	110% LOAD
11.8 L/h	17.1 L/h	22.6 L/h	24.9 L/h

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
1880 x 720 x 1440	1120 kg	175 L

Reference frame 9062GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
1104C-44TAG2	Leroy Somer TAL044D	400 / 3	110	100

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.
DGGB technical specification | Reviewed 2026-10-12

Exact build, performance and delivery scope are confirmed in the quotation.