DGGB220BS

220 kVA

ROUNDED CATALOGUE CLASS

Baudouin diesel generator | Acoustic canopied

NEW DIESEL GENERATOR RANGE



Representative DGGB enclosure; final build may vary.

SELECTED CONFIGURATION

ENGINE

Baudouin 6M16G2D0/S

ALTERNATOR

Stamford UCI274H1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

PRIME POWER / PRP

200 kVA 160 kW

STANDBY POWER / ESP

220 kVA 176 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The DGGB model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	220	176	200	160
200	PS	220	176	200	160
208	PS	220	176	200	160
220	SD	220	176	200	160
230	SD	220	176	200	160
240	SD	220	176	200	160
380	SS	220	176	200	160
400	SS	220	176	200	160
415	SS	220	176	200	160

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Exact build, performance and delivery scope are confirmed in the quotation.

Technical specification

DGGB220BS | Baudouin 6M16G2D0/S | Acoustic canopied

ENGINE

Manufacturer	Baudouin
Model	6M16G2D0/S
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	6
Arrangement	In Line
Displacement	9.726L
Bore	126mm
Stroke	130mm
Compression ratio	17:1
Cooling	Liquid Cooled
Coolant capacity	42L
Oil capacity	30L

ALTERNATOR

Manufacturer	Stamford
Model	UCI274H1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD	75% LOAD	100% LOAD	110% LOAD
22.4 L/h	32.4 L/h	43.1 L/h	46.9 L/h

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
3958 x 1504 x 2384	3020.75 kg	500 L

Reference frame 2900E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
6M16G2D0/S	KWise C274G160	400 / 3	220	200
6M16G2D0/S	Leroy Somer TAL044M	400 / 3	220	200

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.
DGGB technical specification | Reviewed 2026-10-12

Exact build, performance and delivery scope are confirmed in the quotation.