DGGB670S

670 kVA

ROUNDED CATALOGUE CLASS

Scania diesel generator | Open set

NEW DIESEL GENERATOR RANGE

ENGINE PLATFORM

Scania

DC16093A-02-53

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Scania DC16093A-02-53

ALTERNATOR

Stamford S5L1D-F41

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

613 kVA 490 kW

STANDBY POWER / ESP

674 kVA 539 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The DGGB model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
380	SS	671	537	611	489
400	SS	674	539	613	490
415	SS	674	539	613	490

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Exact build, performance and delivery scope are confirmed in the quotation.

Technical specification

DGGB670S | Scania DC16093A-02-53 | Open set

ENGINE

Manufacturer	Scania
Model	DC16093A-02-53
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	ECU
Cylinders	8
Arrangement	At Vee
Displacement	16.4L
Bore	130mm
Stroke	154mm
Compression ratio	16.7:1
Cooling	Liquid Cooled
Coolant capacity	68L
Oil capacity	48L

ALTERNATOR

Manufacturer	Stamford
Model	S5L1D-F41
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1.0% Regulation%
Insulation class	H
Excitation	Brushless
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD	75% LOAD	100% LOAD	110% LOAD
60.4 L/h	88.2 L/h	120.1 L/h	135.6 L/h

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

REFERENCE WEIGHT	FUEL TANK
3578.8 kg	730 L

Reference frame 9007GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
DC16093A-02-53	Stamford S5L1D-E41	400 / 3	665	610

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.
DGGB technical specification | Reviewed 2026-10-12

Exact build, performance and delivery scope are confirmed in the quotation.